

Perfect Doorphone choice for daily life

Akuvox's Audio Doorphone R23C is an open, non-proprietary IP-based door station for two-way communication and remote entry control. It is a perfect complement to any SIP system and offers new possibilities to effectively control entry to your premises.

At a Glance

- Vandal resistant body, with a flush button;
- PoE (IEEE802.3af, Power-over-Ethernet);
- Two-way audio communication over IP networks with Echo Cancel feature;
- Complies with SIP standard for easy integration in every SIP capable PBXes;



Physical & Power

- Front panel: Aluminum
- Button: 1 call button
- Wiegand port: Support
- RS485 port: Support
- RF card reader: 13.56MHz
- Relays out: 2
- Inputs: 3
- Microphone: -40dB
- Speaker: 8Ω / 2W
- Ethernet port: RJ45, 10/100Mbps adaptive
- Power out: 12V/400mA
- 802.3af Power-over-Ethernet
- 12V DC connector (if not using PoE)
- Water-proof & Dust-proof: IP65
- Installation: Flush-mounted or Wall-mounted
- Flush-mounted DIM: 213x124x68mm
- Wall-mounted DIM: 190x110x40mm
- Working Humidity: 10~90%
- Working Temperature: -20°C ~ +55°C
- Storage Temperature: -40°C ~ +70°C